



The X-Tinguish® X-Treme is used by Firefighters, Police, Armed forces and First Responders as a highly effective fire suppression tool against early stage and fully developed fires. The X-Tinguish® X-Treme is non-pressurized and is deployed manually by pulling a pin which will set off an electronic ignition system.

After triggering the X-Tinguish® X-Treme, an aerosol mist is generated, which expands volumetrically, flooding the space and suppressing the flames within seconds. The X-Tinguish® X-Treme is designed for the use on class A, B, C and K fires. In an enclosure up to 5,300Cu.Ft.

“PULL THE PIN AND THROW IT IN!”

Instant Fire suppression within seconds.



When water is on the way and the field is extremely dangerous!

FIRE SUPPRESSION TECHNOLOGY

- does not remove oxygen
- does not utilize super cooling gases
- is not harmful to people or animals
- is not harmful to the atmosphere
- Zero ODP and Zero GWP
- does not increase pressure
- Non-toxic, non-conductive, non-corrosive
- Ignition method: Manual pull-pin, battery

Flame Guard USA
1000 Butterfield Rd.
Suite 1029
Vernon Hills, IL 60061 USA
Ph: (011) 815-219-4074
Fax: (011) 847-387-3824
URL: <https://www.flameguardusa.com>
Email: sales@flameguardusa.com



The World's Most Advanced Aerosol Firefighting Tool!

- COVERAGE UP TO 5,300 CU.FT.
- NO PYROTECHNIC IGNITER!
- WATER RESISTANT SHELL
- BATTERY START!
- RUGGED STEEL BODY CONSTRUCTION
- OPERATES TO -65°F
- FULLY WARRANTIED
- DEPLOYS AFTER 8 SECOND DELAY
- THE SAFEST AEROSOL FIREFIGHTING TOOL AVAILABLE TODAY!!



MAIN FEATURES

The X-Tinguish® X-Treme

- Offers extraordinary knock down as well as fast suppression capabilities
- Reduces temperatures by as much as 1,000°F in 30 seconds
- Can cut water usage by as much as 80%, when used properly
- Aerosol Is SNAP listed by the US EPA
- Is environmentally friendly (ODP 0%, GWP 0%)
- Does not reduce or deplete (O²) oxygen
- Can eliminate flashover and backdraft
- Is Non-Toxic, Non-Corrosive, Non-Conductive
- Highly Efficient and Suitable against A-B-C-K class fires
- **IS NOT** pressurized!
- Has a 5-year battery life
- Has a 15-year shelf life
- Includes a new "R-pin" that protects igniter pin from being accidentally removed.
- LED light turns red when the unit is activated!



SPECIFICATIONS

Total weight	13.90Lbs. / 6.3 kg.
Compound weight	6.40 Lbs. / 2.9 kg.
Volume coverage (up to)	≤ 5,300cu.ft. / 150 m ³
Discharge time	33 seconds
Activation method	Manual pull pin
Operational to	-65°F / -55°C below zero

